























Wireless Communication	Image	Description	Model	Schedule Options			User Interface	Application											Power Method	Features								
				Program Options	Temporary Override	Permanent Hold		Vacation Hold	Stages	Gas, Oil or Electric	Heat Pump	750 Millivolt*	Linevolt	Selectable Residential and Light Commercial	Dual fuel	Balance Point Lockout	Upstage Timer & Droop Settings	Humidification Control		Dehumidification Control	Ventilation Control	Demand Response	Permanent Memory Retention	Selectable Auto or Manual Changeover	Auxiliary Heat Lockout	Adaptive Intelligent Recovery	Temperature Setpoint Limits	Keypad Lockout
WiFi & RedLINK® 3.0		T10+ Thermostat, EIM, RATS/DATS, Wireless Indoor Sensor	YTHM1004R3000	Geofence, 7 day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 4H/2C Heat Pump Up to 3H/2C Conventional	•	•	•			•	•	•	•	•	•	24 volt to R and C at thermostat and EIM	•	•	•	•	•	•	•
		T10+ Thermostat, EIM, RATS/DATS, Wireless Indoor Sensor, Wireless Outdoor Sensor	YTHM1004R3001	Geofence, 7 day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 4H/2C Heat Pump Up to 3H/2C Conventional	•	•	•			•	•	•	•	•	•	24 volt to R and C at thermostat and EIM	•	•	•	•	•	•	•
		T10+ Pro Smart with RedLINK® Sensor	THX321WFS3001W	Geofence, 7 day, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•			•	•	•	•	•	•	C-Wire	•	•	•	•	•	•	•
	T10+ Pro Smart without Sensor	THX321WF3003W	C-Wire																		•	•	•	•	•	•	•	•
WiFi		T6 Pro Smart	TH6320WF2003	Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•									C-Wire	•	•	•	•	•	•	•
	TH6220WF2006		Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Touchscreen	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•											C-Wire	•	•	•	•	•	•
		FocusPRO® S200 Thermostat	TH2110WF4008	Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Soft Keys or Through App	1 Heat/1 Cool	•	•	•									C-Wire	•	•	•	•	•	•	
	TH2320WF4010		Geofence, 7-day, 5-1-1, 5-2, 1 week, no schedule	•	•	Through app	Soft Keys or Through App	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•											C-Wire	•	•	•	•	•	
		9000 Smart	TH9320WF5003	7-Day or NP	•	•	•	Touchscreen	Up to 2 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•										C-Wire	•	•	•	•	•	•
		Vision PRO® 8000 Smart	TH8321WF1001	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•										C-Wire	•	•	•	•	•	•
RedLINK® 1.0/2.0 Accessories		Prestige® IAQ Kits	YTHX9421R5085WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•									24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•	•
	YTHX9421R5101WW		7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•											24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•
	YTHX9421R5127WW		7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•											24 volt to R and C at thermostat and EIM	•	•	•	•	•	•
	YTHX9421R7001WW		7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•											24 volt to R and C at thermostat and EIM	•	•	•	•	•	•
		Prestige® IAQ	THX9421R5021WW	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	•	•	•										24 volt to R and C at thermostat and EIM	w/ Gateway	•	•	•	•	•
		RedLINK® VisionPRO® 8000	TH8110R1008	7-Day or NP	•	•	•	Touchscreen	1 Heat/1 Cool**	•	•	•										Dual powered (battery and hardware)	w/ Gateway	•	•	•	•	•
	TH8320R1003		7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•												Dual powered (battery and hardware)	w/ Gateway	•	•	•	•
	TH8321R1001		7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•												Dual powered (battery and hardware)	w/ Gateway	•	•	•	•
	YTH8321R1002		7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional*	•	•	•												Dual powered (battery and hardware)	•	•	•	•	•
		FocusPRO® 6000							Up to 2 Heat/2 Cool – Heat Pump													Dual powered (battery and hardware)						

# Non-Connected Thermostats

	Description	Model	Scheduling	User Interface	Application					Power Method				Sensors			Temperature Setpoint	
					Stages	Gas, Oil or Electric	Heat Pump	750 Millivolt*	Linevolt		Permanent Memory Retention	Selectable Auto or Manual Changeover	Duel Fuel	Wired Outdoor Sensor	Wired Indoor Sensor	Floor / Slab Sensor		
	T6 Pro	TH6320U2008	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	Lockouts only, no display	•		•	
		TH6220U2000	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	Lockouts only, no display	•		•	
		TH6210U2001	7-Day, 5-1-1, 5-2, or NP	Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•						•
	T6 Pro Hydronic	TH6100AF2004	7-day, 5-1-1, 5-2, or NP	Soft keys	1 Stage Hot Water Heat Only – No Fan					Dual powered (battery and hardwire)	•				•		•	
	FocusPRO® P200 Thermostat	TH2110U4004	7-day, 5-1-1, 5-2, 1 week, no schedule	Soft Keys	1 Heat/1 Cool	•		•		Dual powered (battery and hardwire)	•	•					•	
		TH2210U4005	5-1-1 Day, 5-2 Day, 7 Day, 1 Week, no schedule	Soft Keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	•				•
		TH2320U4006	7-day, 5-1-1, 5-2, 1 week, no schedule	Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	•				•
	FocusPRO® N100 Thermostat	TH1110U4000	No Schedule	Soft Keys	1 Heat/1 Cool	•	•	•		Dual powered (battery and hardwire)	•	•					•	
		TH1210U4001	No Schedule	Soft Keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	•				•
		TH1320U4002	No Schedule	Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	•	•	•				•
	Pro 3000 Non-Programmable	TH3210D1004	NP	Soft keys	2 Heat/1 Cool – Heat Pump only		•			Dual powered (battery and hardwire)	•	Manual						
		TH3110D1008	NP	Soft keys	1 Heat/1 Cool – Heat Pump 1 Heat/1 Cool – Conventional	•	•	•		Dual powered (battery and hardwire)	•	Manual						
	The Round™	T87K1007	NP	Dial	1 Heat or 1 Cool	•				Power stealing							5001094	
		T87N1000	NP	Dial	1 Heat/1 Cool	•				Power stealing		Manual					5001094	
		T87N1026	NP	Easy-To-See™	1 Heat/1 Cool	•				Power stealing		Manual					5001094	
	Econostat Horizontal	T8034N1007	NP	Slide switches and lever	1 Heat/1 Cool	•				Mechanical		Manual					5001966	
	Econostat	T822K1000	NP	Slide switches and lever	1 Heat	•				Mechanical		Positive off					5001966	
		T827K1009	NP	Slide switches and lever	1 Heat	•		•		Mechanical		Positive off					5001966	
	TL8230	TL8230A1003	7-Day	Soft keys	1 Heat				•	3328 watts @ 208 VAC Max 3840 watts @ 240 VAC Max	•	Positive off						
	LineVoltPRO™	TL7235A1003	NP	Horizontal lays	1 Heat				•	3600 watts @ 240 VAC Max 3120 watts @ 208 VAC Max	•	Positive off						
	Line Volt 5-2 Programmable	TH105PLUS	5-2	Buttons	1 Heat				•	3500 watts @ 240 VAC Max 1700 watts @ 120 VAC Max	•						•	